www.soapqueen.eu

SAFETY DATA SHEET DEB 96% (DENATURED ETHANOL B) TSDA-1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Denatured Ethanol B - DEB 96% - TSDA-1

Product number 70022 - OVL16

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Concentrated material for manufacturing purposes only.

1.3. Details of the supplier of the safety data sheet

SUPPLIER SoapQueen vof

Veilingdreef 20

4614 RX Bergen op Zoom

Nederland

CONTACT PERSON Regulatory Manager (Aanwezige leidinggevende)

1.4. Emergency telephone number

EMERGENCY TELEPHONE +31 (0)164 254900 - Office Hours: 09:00 - 17:00 (weekdays only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225
Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing.

Rinse skin with water/ shower.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to

extinguish.

P501 Dispose of contents/ container in accordance with national regulations.

Supplementary precautionary

statements

P240 Ground/ bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P403+P235 Store in a well-ventilated place. Keep cool.

DEB 96% (DENATURED ETHANOL B) TSDA-1

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ALCOHOL 60-100%

CAS number: 64-17-5 EC number: 200-578-6 REACH registration number:

012119457610-43-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F; R11

T-BUTYL ALCOHOL <1%

CAS number: 75-65-0 EC number: 200-889-7 REACH registration number:

012119444321-51-XXXX

Classification (67/548/EEC or 1999/45/EC)

F; R11. Xn; R20. Xi; R36/37

Classification

Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Eye Irrit. 2 - H319 STOT SE 3 - H335

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention

immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get

medical attention if symptoms are severe or persist after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of

water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

4.2. Most important symptoms and effects, both acute and delayed

General information Persons suffering from asthma, eczema or skin problems should avoid contact, including

dermal contact, with this product. See Section 11 for additional information on health hazards.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder.

Unsuitable extinguishing

Water.

media

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours.

DEB 96% (DENATURED ETHANOL B) TSDA-1

5.3. Advice for firefighters

Protective actions during

firefighting

Containers close to fire should be removed or cooled with water.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. No smoking, sparks, flames or other sources of ignition near

spillage.

6.2. Environmental precautions

Environmental precautions

Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Keep combustible materials away from spillage. Eliminate all sources of ignition. Provide adequate ventilation. Contain and absorb spillage with sand, earth or other non-combustible material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with

skin, eyes and clothing.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Wash at the end of each work shift and

before eating, smoking and using the toilet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away

from heat, sparks and open flame. Protect from freezing and direct sunlight.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ALCOHOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

T-BUTYL ALCOHOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 308 mg/m³ Short-term exposure limit (15-minute): WEL 150 ppm 462 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment







DEB 96% (DENATURED ETHANOL B) TSDA-1

Appropriate engineering

controls

Provide adequate ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn

if a risk assessment indicates skin contact is possible.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective

clothing in case of contact.

Hygiene measures No specific hygiene procedures recommended but good personal hygiene practices should

always be observed when working with chemical products.

Respiratory protection No specific recommendations. Respiratory protection may be required if excessive airborne

contamination occurs.

Environmental exposure

controls

Residues and empty containers should be taken care of as hazardous waste according to

local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Colourless.

Odour Characteristic.

Flash point 12°C

Relative density ~ 0.812 @ 20°C

9.2. Other information

Refractive index ~ 1.360 @ 20°C

SECTION 10: Stability and reactivity

10.1. Reactivity 10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Will not polymerise.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

products vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information No specific health hazards known.

DEB 96% (DENATURED ETHANOL B) TSDA-1

Inhalation No specific health hazards known.

Ingestion No specific health hazards known. No harmful effects expected from quantities likely to be

ingested by accident.

Skin contact No specific health hazards known.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health

hazards

No specific health hazards known.

Medical symptoms No specific symptoms noted, but this chemical may still have adverse health impact, either in

general or on certain individuals.

Medical considerations May cause allergic contact eczema. Prolonged or repeated exposure may cause the

following adverse effects: Allergic rash. Get medical attention.

SECTION 12: Ecological Information

Ecotoxicity No negative effects on the aquatic environment are known.

12.1. Toxicity 12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable. The product contains substances which are not

expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1170 UN No. (IMDG) 1170 UN No. (ICAO) 1170 UN No. (ADN) 1170

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

€

ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Proper shipping name (IMDG) ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Proper shipping name (ICAO) ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Proper shipping name (ADN) ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

DEB 96% (DENATURED ETHANOL B) TSDA-1

14.3. Transport hazard class(es)

ADR/RID class

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group

IMDG packing group Ш

ADN packing group Ш

ICAO packing group Ш

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-D

ADR transport category 2

Emergency Action Code •2YE

Hazard Identification Number 33

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to

Annex II of MARPOL 73/78

and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Guidance Workplace Exposure Limits EH40.

DEB 96% (DENATURED ETHANOL B) TSDA-1

15.2. Chemical safety assessment

SECTION 16: Other information

Key literature references and

European Chemicals Agency, http://echa.europa.eu/

sources for data

Issued by Regulatory Manager

Revision date 25/06/2018

Revision 0

Hazard statements in full H225 Highly flammable liquid and vapour.

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.